

# GUMMI SUGESLANGE

KATALOG 9

## Gummi sugeslange med muffer

Sugeslange i SBR-gummi med helix ståls spiral og 2 bløde muffer.  
Glat indvendig, korrugeret spiral udvendig.  
Max. vakuum 0,9 bar  
Temperaturområde -30° til +80° C.



9

Varenr.	Dimension indv.		Godstykkeelse [mm]	Arbejds tryk [bar]	Bøjnings radius mm	Meter pr. længde
	tomme	mm				
16013002	3"	76	6	3	608	2
16013003	3"	76	6	3	608	3
16013004	3"	76	6	3	608	4
16013005	3"	76	6	3	608	5
16013006	3"	76	6	3	608	6
16014002	4"	102	7	3	816	2
16014003	4"	102	7	3	816	3
16014004	4"	102	7	3	816	4
16014005	4"	102	7	3	816	5
16014006	4"	102	7	3	816	6
16015002	5"	127	8	3	1016	2
160150022	5"	127	8	3	1016	2,2
16015003	5"	127	8	3	1016	3
16015004	5"	127	8	3	1016	4
16015005	5"	127	8	3	1016	5
16015006	5"	127	8	3	1016	6
16016002	6"	152	9	3	1216	2
16016003	6"	152	9	3	1216	3
16016004	6"	152	9	3	1216	4
16016005	6"	152	9	3	1216	5
16016006	6"	152	9	3	1216	6
16018001	8"	203	11	3	1624	1
1601800125	8"	203	11	3	1624	1,25
160180015	8"	203	11	3	1624	1,5
1601800175	8"	203	11	3	1624	1,75
16018002	8"	203	11	3	1624	2
160180025	8"	203	11	3	1624	2,5
16018003	8"	203	11	3	1624	3
160180035	8"	203	11	3	1624	3,5
16018004	8"	203	11	3	1624	4
160180043	8"	203	11	3	1624	4,2
16018005	8"	203	11	3	1624	5
16018006	8"	203	11	3	1624	6
16019001	10"	254	13	3	2032	1
16019002	10"	254	13	3	2032	2
16019004	10"	254	13	3	2032	4
16019005	10"	254	13	3	2032	5
16019006	10"	254	13	3	2032	6
160190065	10"	254	13	3	2032	6,5

